RECESSED SHOWER PANEL





- Compact size custom sizes available
- Supplied complete, ready to install
- Anti ligature and Vandal Resistant
- Single and Adjustable Temperature Valves options.
- Integrated recessed stainless soap holder
- Grade 304 satin stainless steel
- Suits security and parks and recreation projects



The *BRITEX Recessed Shower Panel* is a practical fixture, suitable for a range of project applications. It is supplied complete with an anti-ligature, vandal resistant shower head, single temperature valve (as standard) and integrated recessed stainless soap holder. An adjustable temperature valve is available as an option. Supplied as a unit, and ready to install. Manufactured from commercial grade 304 stainless steel. Custom panel sizes available on request.



BRITEX S.S. Recessed Shower Panel - 11"[267] x 20"[520] x 4"[102]. Supplied complete with antiligature, vandal resistant shower head, single temperature valve and integrated recessed soap holder - Product Code US-BSPR

*RED TEXT may denote a variable where one option only is to be selected, a nominal dimension that needs to be specified, or an optional feature that can be removed if not required. Please refer to the back of this page for additional specification details and options.

VISIT BRITEXUSA.COM TO DOWNLOAD THE MOST CURRENT PRODUCT LITERATURE.




TANKS/MISC


RECESSED SHOWER PANEL

PRODUCT CODE






MODEL US-BSPR Front Elevation




MODEL US-BSPR Side Elevation

specifying guide When specifying this product please include: • Product Name and Code • Product Features • Product Dimensions options



MODEL US-BSPR Plan



MODEL US-BSPR Isometric View

Adjustable Tempertaure Valve

VISIT BRITEXUSA.COM TO DOWNLOAD THE MOST CURRENT PRODUCT LITERATURE



Due to ongoing research and our commitment to product development, details are subject to change without notice. Details accurate at time of print. Please refer to britexusa.com for the most current product information. Allow +/- 5mm tolerance for dimensions and setouts shown in product literature All dimensions shown in inches ["] are of approximate value only.