## **ABLUTION TROUGH**





Image shows Model TABL-U Boxed Upstand to Rear



- · Available pre-plumbed with tapware
- Available with or without upstand
- Standard and custom lengths
- Upstand model conceals tapware connections
- 50mm waste & wall brackets supplied
- Radius internal corners easy cleaning
- Left or right hand waste position
- Ideal for schools, public amenities and pavilions



The BRITEX Stainless Steel Ablution Trough also known as the Pattern No. 5 trough is a versatile wash trough with rounded internal corners that prevent build up of grime and ensure cleaning is easy. A 50mm hob is provided in the splashback of the TABL-U so that plumbing can be concealed behind the trough without needing to make penetrations in the wall behind. Made from 1.2mm type 304 stainless steel and possessing square external corners it is available in custom lengths with either left or right hand waste position.



BRITEX 1.2mm grade 304 S.S. Ablution Trough - XXXXL x 485W x 215D. Complete with left/right hand 50mm waste outlet and wall mounting brackets - Product Code TABL

\*RED TEXT may denote a variable where one option only is to be selected, a nominal dimension that needs to be specified, or an optional feature that can be removed if not required. Please refer to the back of this page for additional specification details and options.

VISIT BRITEX.COM.AU TO DOWNLOAD BIM FILES, CAD DRAWINGS AND THE MOST CURRENT PRODUCT LITERATURE



MELBOURNE Britex Place, Mirra Crt Bundoora VIC 3083 t (03) 9466 9000 f (03) 9466 9044 SYDNEY
16 Northumberland Drv
Taren Point NSW 2229
t (02) 9531 2100
f (02) 9531 2800

PERTH
Unit 1/8 Principal Link
Malaga WA 6090
t (08) 9249 5464
f (08) 9248 6893

BRISBANE
19 Manilla St
East Brisbane QLD 4169
t (07) 3363 2400
f (07) 3363 2444

ADELAIDE
The Britex Group
SA State Office
t 1300 764 744
f 1300 784 306

# **ABLUTION TROUGH**

PRODUCT CODE

#### TABL Standard Ablution Trough


## **TABL-U** Ablution Trough with boxed

#### Suggested Mounting Heights (mm)


	infant	primary	secondary
wash	550	650	700




Troughs over 2000mm long are supplied with a centre support bracket



MODEL TABL Section




MODEL TABL Front Elevation and Plan





MODEL TABL-U Front Elevation and Plan



MODEL TABL-U Section

#### When specifying this product please include:

- specifying guide
- Product Name and Code
- Product Dimensions
- Tapware details (if required)
- Position of Waste Outlet (left/right)



- Standard Sizes (1200, 1500, 1800, 2400mm)
- Tapware See Tapware Section: 11
- Tap holes
- Support legs
- Custom trough dimensions
- · Left or right hand waste outlet

VISIT BRITEX.COM.AU TO DOWNLOAD BIM FILES, CAD DRAWINGS AND THE MOST



